

TECHNICAL SHEET



NEW SUNBRELLA

Boat equipment

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	100% Sunbrella solution dyed acrylic			
Finish	special marine treatment			
Weave	Canvas			ISO 7211-1
Weight	315		g/m ²	ISO 2286-1
Width	152		cm	EN 1773

FABRIC STRENGTH

Oil-repellent properties	5		class /8	ISO 14419
Tensile strength	155	100	daN	ISO 13934-1
Tear strength	4.6	2.5	daN	ISO 13937-1
Elongation at break	34	24	%	ISO 13934-1
Schmerber	380		mm	ISO 811
Spray test	4-5		class /5	ISO 4920

COLOUR RESISTANCE

Colour fastness UV	7-8		class /8	ISO 105 B02
Colour fastness weather condition	7-8		class /8	ISO 105 B04
Colour fastness under dry friction	5		class /5	ISO 105X12
Colour fastness under wet friction	5		class /5	ISO 105X12

USE

Roll length	60	Im		
Recommended use	Cockpit cover, spray hood, bimitop, Sun awning, flybridge, dodgers, winch cover, Mainsail cover.			
Guarantee	10	Years		

The values for this product may have a variation of +/-5%.

Dickson - Constant

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com

SUNACRYL®
OUTDOOR FIBRE
by DICKSON®

FINISHING
CLEANGARD®
OUTDOOR TREATMENT
by DICKSON®

